



QOLTEC ADAPTER FIBER OPTIC HYBRID LC/UPC - FC/UPC | SIMPLEX | SINGLEMODE

	-, EUR
SHIPPIN	IG TIME: 24 HOURS
CATALOG	NUMBER: 54149
EAN COD	E: 5901878541495
TYPE CON	NNECTORS: LC/UPC - FC/UPC
TYPE: SIM	IPLEX
FIBER TYI	PE: JEDNOMODOWY
ADDITION	VAL INFORMATION: EASY INSTALLATION AND
HANDLIN	G. CAN BE USED IN HIGH SPEED FIBER OPTIC
TRANSMI	SSION NETWORKS.
PACKAGE	: POLYBAG
	E POLYBAG
PRODUCE	
PRODUCE	ENT: QOLTEC
PRODUCE GWARAN SZEROKO	CJA: 24 MIESIĄCE
PRODUCE GWARAN SZEROKC GŁĘBOKC	ENT: QOLTEC CJA: 24 MIESIĄCE DŚĆ OPAKOWANIA [MM]: 15
PRODUCE GWARAN SZEROKC GŁĘBOKC WYSOKO	ENT: QOLTEC CJA: 24 MIESIĄCE DŚĆ OPAKOWANIA [MM]: 15 DŚĆ / DŁUGOŚĆ OPAKOWANIA [MM]: 40

ITEM DESCRIPTION

PRODUCT DESCRIPTION

IT IS USED TO CONNECT SINGLEMODE OR MULTIMODE FIBER OPTIC CABLES WITH LC/UPC – FC/UPC CONNECTORS, WHICH ARE MOSTLY USED IN DISTRIBUTIONS FRAME, CONNECTING PATCHCORDS WITH PIGTAILS WELDED WITH OPTIC CABLE. SINGLEMODE ADAPTERS ARE MADE OF BRONZE HOUSING AND CERAMIC SLEEVES AND IT IS MORE PRECISE THAN MULTIMODE ADAPTER. IT CAN BE USED WITH FIBRE OPTIC PATCHCORDS, WHICH SEND HIGH-SPEED DATA THROUGH A NETWORK.

SCHEME SINGLEMODE FIBER

SINGLEMODE FIBER HAS A SMALL CORE DIAMETER THAT SUPPORTS ONLY ONE MODE OF LIGHT. SIGNAL IS TRAVELING IN A SINGLE LIGHT BEAM WITH CLOSE TO NONE REFLECTION. LOW REFLECTION RATIO MEANS LOWER DISPERSION. THAT MAKES THEM PERFECT FOR LONG DISTANCE BECAUSE SIGNAL CAN BE TRANSMITTED WITHOUT USAGE OF FIBRE AMPLIFIER EVEN TO 100 KM.